SPRING COLOR

FINITURE NATURALI DAL 1992

FACTORY

BREATHABLE PAINT

DESCRIPTION

Product suitable for use on all interior surfaces.
The vinyl resin it is composed of provides resistance to alkalis and good scrub resistance, as well as sanitizing and anti-mould properties. FACTORY is a breathable paint, specifically formulated for professional use, featuring high coverage, ease of application, good flow, and the ability to provide a uniform matt finish even on surfaces with uneven absorption.

RECOMMENDED USES

Applicable on:

- New and old plasters based on hydraulic binders.
- Concrete surfaces.
- Gypsum and plasterboard surfaces.
- Existing paints and coatings of organic or mineral nature, provided they are dry, sound, absorbent and well-adhered.
- Various mineral-based substrates, provided they are absorbent. Surfaces must be properly prepared.

Do not apply on fresh or highly alkaline substrates; allow adequate curing time, generally four weeks.

TECHNICAL CHARACTERISTICS

Drying time (at 25 °C and 65% R.H.): touch dry in 1 hour; recoatable after 6–8 hours.

SUBSTRATE PREPARATION

Ensure that the substrate is completely dry and cured. If necessary, repair or consolidate using suitable products.
In the presence of mould, treat the surface with PRIMAVERA cleaner.
Remove any efflorescence and flaking parts of old paint by brushing or washing. Completely remove thick layers of lime-based or distemper paints.
Remove dust, smog and other deposits by brushing.
Plaster, gypsum and plasterboard surfaces:

- Level any irregularities and repair holes, cracks and depressions.
- Sand fillers and patch repairs with sandpaper.

SPRING COLOR

FINITURE NATURALI DAL 1992

- Seal cracks with suitable sealants.
- Apply skim coats where necessary.

On clean and dry surfaces apply:

- For interior use, one coat of Fissativo.

(Dilution of the primer and the quantity to be applied depend on the absorbency of the substrate and must be determined by preliminary tests on the specific surface – refer to the relevant technical data sheet).

APPLICATION INSTRUCTIONS

Environmental and substrate conditions:

- Ambient temperature: Min. +8 °C / Max. +35 °C
- Relative humidity: < 75%
- Substrate temperature: Min. +5 °C / Max. +35 °C
- Substrate moisture: < 10% Avoid application under direct sunlight.

Tools: brush, roller, spray.

Number of coats: at least 2 coats.

Dilution:

- First coat: 20% with water
- Subsequent coats: 30% with water

For airless application, dilution may vary depending on equipment and operating pressure.

- Clean tools immediately after use with water.
- Indicative coverage: 8–10 m²/l per coat, referring to smooth and moderately absorbent substrates. Actual coverage should be determined by preliminary testing on the specific substrate.

TINTING

The product can be tinted using our tinting system.

STORAGE

Maximum storage temperature: +30 °C

Minimum storage temperature: +5 °C

The product should preferably be used within 2 years from the production date if stored in original unopened containers under proper temperature conditions.

SAFETY INSTRUCTIONS

Use the product in accordance with current hygiene and safety regulations. After use, do not dispose of containers in the environment; allow residues to dry thoroughly and dispose of them as special waste. Keep out of reach of children. Use in well-ventilated areas. In case of contact with eyes, rinse immediately with plenty of water. In case of ingestion, seek medical advice immediately and show the container or label. Do not dispose of residues in drains, watercourses or soil. For further information, refer to the safety data sheet.