SPRING COLOR

FINITURE NATURALI DAL 1992

PITTURA SUGHERO (cork paint)

TEXTURED PAINT FOR INTERIOR USE

DESCRIPTION

Cork Paint is a decorative finish with a slight thermal effect determined by the presence of cork. It is composed of aged lime putty, calcium carbonates, and micronized cork. Cork Paint provides a textured aesthetic effect while maintaining the delicacy and refinement of a premium material. It gives the environment a pleasant sensation of warmth, thanks to its natural origin and its characteristic amber color. Product for indoor use.

COMPONENTS

Micronized cork, marble powder, calcium carbonates, lime putty, siliceous sand, cellulose thickener, vinyl dispersion, starch, wetting agent, dispersant.

SURFACE PREPARATION AND APPLICATION

For correct and long-lasting application of the product, follow these guidelines:

- The surfaces to be treated must be sound, consistent, homogeneous, clean, free from mold, lichens, greasy and/or oily residues, dust or particles of any kind, and free from rising damp. All incoherent and unstable parts must be removed to restore optimal substrate suitability, a necessary condition for correct product application.
- Cork Paint cannot adhere to existing old or new paint layers unless their perfect adhesion, necessary absorption, and tensile strength capacity of the mineral coating are verified. If the underlying layers do not meet these requirements, total or partial removal is recommended.
- On new lime and cement-based plasters, apply our Fissativo and subsequently our Primer Centri Storici.
- On natural hydraulic lime and lime putty-based plasters, apply our Primer Centri Storici.
- On substrates where surface uniformity is required, both in the presence of small imperfections or absorption irregularities, apply our Fissativo followed by our Primer Centri Storici.

SPRING COLOR

FINITURE NATURALI DAL 1992

- On gypsum-based finished surfaces, verify on-site compatibility with Cork Paint; in case of pronounced powdering or abnormal absorption, treat with our Fissativo followed by our Primer Centri Storici.
- On drywall and fiberboard plaster, it is optimal to skim coat the entire surface with our Stucco Naturale. Then proceed with our Dura Gypsum.

Mix well before and during use.
Allow 6-8 hours between coats, ensuring the surface is uniformly dry. Surface temperatures should be between 7°C and 30°C, with ambient humidity below 80%, both during application and for the subsequent 48 hours.

APPLICATION DATA

DILUTION: maximum 5% with water
YIELD: 4-6 m²/liter per coat, depending on substrate absorption
TOOLS: brush

GENERAL FEATURES

COLOR: amber
PACKAGING: 12-liter bucket, 4-liter bucket, 0.8-liter can
STORAGE: 12 months in original, intact packaging, protected from freezing (near 0°C), temperatures above 30°C, and excessively humid environments.
COLORING: Achievable with all colors from the color chart. Note: the base color of the Cork Line is amber, so it is necessary to **REQUEST A SAMPLE** to evaluate the final color effect.
PRODUCTION SITE: Spring Color headquarters, Via Jesina 63, Castelfidardo (Ancona)
PACKAGING SITE: Spring Color headquarters, Via Jesina 63, Castelfidardo (Ancona)
Specific Weight: 1.583 kg/l

SPECIFICATION ITEM

Cork Paint is a decorative finish with a slight thermal effect determined by the presence of cork. Composed of aged lime putty, calcium carbonates, and micronized cork. Cork Paint provides a textured aesthetic effect while maintaining the delicacy and refinement of a premium material. It gives the environment a pleasant sensation of warmth thanks to its natural origin and characteristic amber color.
DILUTION: maximum 5% with water
YIELD: 4-6 m²/liter per coat
TOOLS: brush

SPRING COLOR

FINITURE NATURALI DAL 1992

PRODUCT COLORING

Spring Color tints are made from natural pigments and produced artisanally.

Any variations in shade are due to the natural variability of the earth pigments and raw materials, the substrate, the correct dispersion process, the origin of the pigments, climatic conditions, and the applicator's experience.

In lime-based products, color variability is greater; it is recommended to test color fidelity and, if necessary, adjust the tint accordingly.

Spring Color colors its finishes using selected and tested earths and oxides. The use of other types of colorants or ingredients does not bind the company in any way.

NOTES

The information provided in this technical data sheet is based on our own practical experience. However, it is intended as a general guideline and should not be considered exhaustive. Spring Color reserves the right to make technical modifications without prior notice. This technical data sheet cancels and replaces all previous editions. Spring Color accepts no responsibility for improper use of the products. This document is for informational purposes only and cannot be used as grounds for legal claims.
Since we cannot directly control site conditions or the execution of application processes, the information provided must be considered general and non-binding. We therefore recommend carrying out one or more preliminary tests to verify the suitability of the product for the intended use.
This product complies with Legislative Decree No. 161 of March 26, 2006: VOC <30 g/L.

WARNINGS

- Keep out of reach of children.
- All components can be disposed of through standard waste management systems.
- Avoid disposing of product residues into the sewage system.
- Do not ingest. Avoid contact with skin and eyes.
- Ensure good ventilation during and after application.
- Protect surfaces that are not to be painted.

Refer to the safety data sheets (SDS).

SPRING COLOR

FINITURE NATURALI DAL 1992